# **Airborne Sound Absorption**



# **Acusticell S TE**

## **Applications**

**Industry** Crane Cabins.

**Transport and contracting** Cabins for boats, vehicles, scooters and contractor's machinery.

#### Office

Walls, Office Screens and Furniture.

### Method of use

The parts are cut or stamped to the required shape and carefully pressed on to a surface that must be free from oil, dirt, and dust.

## Product characteristics

Acusticell S TE is a sound absorbing material of foamed polyurethane with open cells.

The product is based on Acusticell S but its surface is covered with a velour textile. The material can be bent and is self-adhesive. Can be combined with a mat for structure-borne sound damping and airborne sound insulation.

#### **Advantages**

- □ Good absorption
- Aesthetically attractive surface
- □ High sense of comfort
- □ UV resistant textile
- Dirt repellent and Easily Cleaned
- Difficult to ignite



#### Working on new measurement

## **Technical data**

Sound absorption	See diagram
Resistance to temperature	$-40^{\circ}$ C to $+ 120^{\circ}$ C
Fire Class	FMVSS 302
Coefficient of thermal conductivity	$\lambda = 0,036 \text{ W/m}^{\circ}\text{C}$
Adhesive's tear strength	Ca 15 N/cm test width
Resistance to light	UV resistent
Colour	Grey
Colour Thickness	Grey 10, 15 or 20 mm (other thickness can be supplied on request)
	10, 15 or 20 mm (other thickness can be supplied on
Thickness	10, 15 or 20 mm (other thickness can be supplied on request)

#### **Experiences**

The shaping and positioning of the material is of major importance to achieve an optimal sound-dampening effect.

SONTECH has long experience of practical noise control projects in a wide range of industrial fields. These experiences can be a valuable addition to the laboratory data given in the datasheet.

SONTECH can also assist with advice and sound measurements for noise control and in the manufacture of customised material sets.

#### **Designation system**

(other thickness can be supplied on	Acusticell	AC
request)	Thickness in mm	10,15 or 20
Freon and PVC free	Fire Class	
Approx 28 kg/m <sup>3</sup>	FMVSS 302	S
1000x1500 mm (other sizes and shapes can be	Example of order code	AC20S TE



Sontech International AB Energivägen 6 SE 196 37 Kungsängen Tel +46 8-445 50 60

info@sontech.se www.sontech.se